

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/15/2011 Revision date: 07/23/2018 Supersedes: 10/23/2017 Version: 3.0 VELTEK ASSOCIATES, INC.

SECTION 1: Identification

Identification

Product form : Mixture

Product name : DECON-QUAT® 200C

Product code SDS VEL-110

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Disinfectant

Cleaning agent

For manufacturing and industrial use only

For professional use only

Supplier 1.3.

Veltek Associates, Inc.

15 Lee Blvd

Malvern, PA 19355-1234 USA

Telephone: +1 610-644-8335 - Fax: +1 610-644-8336

E-mail: vai@sterile.com

In Canada distributed by:

Canada Clean Room (CCR)

200 Terence Matthews

Kanata, ONT K2M 2C6, Canada

Telephone: 888-595-8070

Emergency telephone number

: CARECHEM 24: 1-215-207-0061 Emergency number

1-866-928-0789 (toll free)

Canada: 1-800-579-7421 (toll free) Mexico: +52-55-5004-8763

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS-US classification

H227 Combustible liquid Flammable liquids

Category 4

Acute toxicity (oral) H302 Harmful if swallowed

Category 4

Skin corrosion/irritation H314 Causes severe skin burns and eye damage

Category 1B

Serious eye damage/eye H318 Causes serious eye damage

irritation Category 1

Specific target organ H373 May cause damage to organs (respiratory tract) through prolonged or repeated exposure

(Inhalation)

toxicity (repeated exposure)

Category 2 H401 Toxic to aquatic life

Hazardous to the aquatic

environment - Acute Hazard Category 2

Hazardous to the aquatic H411 Toxic to aquatic life with long lasting effects

environment - Chronic Hazard Category 2

Full text of H statements: see section 16

07/24/2018 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US)









Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H373 - May cause damage to organs (respiratory tract) through prolonged or repeated

exposure (Inhalation)

H401 - Toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.

P260 - Do not breathe vapors.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

P280 - Wear eye protection, protective gloves, protective clothing. P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a doctor

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use Water spray, foam, carbon dioxide (CO2) to extinguish.

P391 - Collect spillage.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an authorized waste collection point

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Didecyldimethylammonium chloride	(CAS-No.) 7173-51-5	7 - 13	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Tetrasodium ethylene diamine tetraacetate	(CAS-No.) 64-02-8	5 - < 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Dam. 1, H318 STOT RE 2, H373
Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides	(CAS-No.) 68424-85-1	5 - < 10	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400
Alcohols, C9-11, branched and linear, ethoxylated	(CAS-No.) 68439-46-3	1 - 5	Eye Dam. 1, H318
Ethanol	(CAS-No.) 64-17-5	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
Citric acid	(CAS-No.) 77-92-9	< 1	Eye Irrit. 2A, H319

07/24/2018 EN (English US) 2/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove person to fresh air and keep at rest in a position comfortable for breathing. If symptoms develop, obtain medical attention.

First-aid measures after skin contact

Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Obtain immediate medical attention.

First-aid measures after eye contact

: Rinse immediately with plenty of water for 15 minutes. Ensure that folded skin of eyelids is thoroughly washed with water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain immediate medical attention.

First-aid measures after ingestion

: Do NOT induce vomiting. Rinse mouth. Give 100 - 200 ml of water to drink. Obtain immediate medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms

: Causes severe skin burns and eye damage. May be harmful in contact with skin. Inhalation of vapors may cause respiratory irritation. Severe irritation or burns to the mouth, throat, esophagus, and stomach. Harmful if swallowed.

Chronic symptoms

May cause damage to organs (respiratory tract) through prolonged or repeated exposure (if inhaled).

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Alcohol-resistant foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard

: Combustible liquid and vapor.

Explosion hazard

On heating, there is a risk of bursting due to internal pressure build-up. Cool down the containers exposed to heat with a water spray.

Reactivity

: Stable under recommended handling and storage conditions (see section 7).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

 Exercise caution when fighting any chemical fire. Keep upwind. Use water spray or fog for cooling exposed containers. Do not allow run-off from fire fighting to enter drains or water courses.

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus when in close proximity to fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Remove all sources of ignition. Ventilate area. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment

: Equip cleanup crew with proper protection. Use chemically protective clothing.

Emergency procedures

: Remove all sources of ignition. Ventilate area. Do not breathe vapors. Do not get in eyes, on skin, or on clothing.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

07/24/2018 EN (English US) 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

SECTION 8: Exposure controls/personal protection. SECTION 13: Disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Provide good ventilation in process area to prevent formation of vapor. Do not

breathe vapors. Do not get in eyes, on skin, or on clothing.

Hygiene measures : Do not eat, drink or smoke when using this product. Handle in accordance with good industrial

hygiene and safety practice. Take off immediately all contaminated clothing and wash it before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking

or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Keep only in the original container in a cool, well

ventilated place away from : Incompatible materials. Store locked up.

Incompatible materials : Strong acids. Strong alkalis. Strong oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)			
ACGIH	Local name	Ethanol	
ACGIH	ACGIH STEL (ppm)	1000 ppm	
ACGIH	Remark (ACGIH)	URT irr	
ACGIH	Regulatory reference	ACGIH 2018	
OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
OSHA	Regulatory reference (US-OSHA)	OSHA	

8.2. Appropriate engineering controls

Appropriate engineering controls

: Provide good ventilation in process area to prevent formation of vapor. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential

exposure.

Environmental exposure controls : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Wear suitable protective clothing.

Hand protection:

Wear chemically resistant protective gloves. The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed. Gloves should be removed and replaced if there are any signs of degradation or breakthrough.

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact. Impervious footwear must be worn

Respiratory protection:

In case of inadequate ventilation: Use an approved air purifying respirator to control exposure. Follow respirator protection requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.

07/24/2018 EN (English US) 4/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Thermal hazard protection:

Not required for normal conditions of use.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Colorless to straw-colored liquid.
Color : Colorless to straw yellow

Odor : Organic

Odor threshold : No data available

pH : 6-8

Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available

Flash point : 155.3 °F (68.5 °C) (Tag closed cup)

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. : No data available Vapor pressure Relative vapor density at 20 °C : No data available Relative density : 1.006 (Water = 1) Solubility : Water: Miscible Log Pow : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available

Viscosity, kinematic : 13.6 mm²/s (22 °C/71.6 °F)

Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended handling and storage conditions (see section 7).

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7). Combustible liquid and vapor.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizing agents. Strong alkalis. Strong acids.

10.6. Hazardous decomposition products

Fire may produce irritating, corrosive and/or toxic gases. Hydrogen chloride. Nitrogen oxides. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

07/24/2018 EN (English US) 5/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Didecyldimethylammonium chloride (7173-51-5)			
LD50 oral rat	329 mg/kg		
LD50 dermal rabbit	> 1000 mg/kg		
Tetrasodium ethylene diamine tetraacetate (64-02-8)			
LD50 oral rat	1780 - 2000 mg/kg		
Alcohols, C9-11, branched and linear, ethoxy	lated (68439-46-3)		
LD50 oral rat	3488 mg/kg (female)(Read-across)		
LD50 dermal rabbit	2000 mg/kg (male)(Read-across)		
LC50 inhalation rat (mg/l)	> 1.6 mg/l - 4 Hours (Read-across)		
Quaternary ammonium compounds, benzyl-0	C12-16-alkyldimethyl, chlorides (68424-85-1)		
LD50 oral rat	426 mg/kg		
Ethanol (64-17-5)			
LD50 oral rat	10470 mg/kg		
LC50 inhalation rat (mg/l)	117 - 125 mg/l - 4 Hours		
Skin corrosion/irritation	: Causes severe skin burns and eye damage.		
	pH: 6 - 8		
Serious eye damage/irritation : Causes serious eye damage.			
	pH: 6 - 8		
Respiratory or skin sensitization	: Not classified		
Germ cell mutagenicity	: Not classified		
Carcinogenicity	: Not classified		
Reproductive toxicity	: Not classified		
Specific target organ toxicity – single exposure	: Not classified		
Specific target organ toxicity – repeated exposure	: May cause damage to organs (respiratory tract) through prolonged or repeated exposure (Inhalation).		
Aspiration hazard	: Not classified		
Potential Adverse human health effects and symptoms	: Causes severe skin burns and eye damage. May be harmful in contact with skin. Inhalation of vapors may cause respiratory irritation. Severe irritation or burns to the mouth, throat, esophagus, and stomach. Harmful if swallowed.		
Chronic symptoms	: May cause damage to organs (respiratory tract) through prolonged or repeated exposure (if inhaled).		

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Didecyldimethylammonium chloride (7173-51-5)		
LC50 fish 0.49 mg/l - 96 Hours (Danio rerio)		
EC50 Daphnia	0.029 mg/l - 48 Hours (Daphnia magna)	
NOEC (chronic)	0.021 mg/l - 21 days (Daphnia magna)	
Tetrasodium ethylene diamine tetraacetate (64-02-8)		
LC50 fish	486 mg/l 96 Hours	

Ethanol (64-17-5)	
LC50 fish 11200 mg/l (calculated value)	
EC50 Daphnia	5012 mg/l (calculated value) (freshwater)
EC50 Daphnia 2	857 mg/l (calculated value) (marine water)

12.2. Persistence and degradability

No additional information available

07/24/2018 EN (English US) 6/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

Alcohols, C9-11, branched and linear, ethoxylated (68439-46-3)	
Log Pow	3.74 (25 °C)

Ethanol (64-17-5)

Bioconcentration factor (BCF REACH) 3

12.4. Mobility in soil

	DECON-QUAT® 200C	
Γ	Ecology - soil	Miscible with water.

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations. Dispose of this material

and its container at hazardous or special waste collection point.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care. Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1903 Disinfectants, liquid, corrosive n.o.s. (Didecyldimethylammonium chloride ; Quaternary

ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides), 8, II

UN-No.(DOT) : UN1903

Proper Shipping Name (DOT) : Disinfectants, liquid, corrosive n.o.s. (Didecyldimethylammonium chloride; Quaternary

ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides)

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive



Dangerous for the environment : Yes
Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Symbols : G

DOT Special Provisions (49 CFR 172.102) : B2, IB2, T7, TP2

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

07/24/2018 EN (English US) 7/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location : B
Emergency Response Guide (ERG) Number : 153

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport document description : UN1903 DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (Didecyldimethylammonium chloride;

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides), 8, II

UN-No. (TDG) : UN1903

Proper Shipping Name (Transportation of : DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (Didecyldimethylammonium chloride;

Dangerous Goods) Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides)

TDG Primary Hazard Classes : 8 - Class 8 - Corrosives
Packing group : II - Medium Danger

TDG Special Provisions : 16
Explosive Limit and Limited Quantity Index : 1 L
Passenger Carrying Road Vehicle or Passenger : 1 L

Carrying Railway Vehicle Index

Transport by sea

Transport document description (IMDG) : UN 1903 DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (Didecyldimethylammonium chloride

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides), 8, II, MARINE

POLLUTANT/ENVIRONMENTALLY HAZARDOUS

UN-No. (IMDG) : 1903

Proper Shipping Name (IMDG) : DISINFECTANT, LIQUID, CORROSIVE, N.O.S. (Didecyldimethylammonium chloride;

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides)

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Marine pollutant : Yes



Air transport

Transport document description (IATA) : UN 1903 Disinfectant, liquid, corrosive, n.o.s. (Didecyldimethylammonium chloride, Quaternary

ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides), 8, II, ENVIRONMENTALLY

HAZARDOUS

UN-No. (IATA) : 1903

Proper Shipping Name (IATA) : Disinfectant, liquid, corrosive, n.o.s. (Didecyldimethylammonium chloride ; Quaternary

ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides)

Class (IATA) : 8 - Corrosives
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

DECON-QUAT® 200C		
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Acute toxicity (any route of exposure) Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation Health hazard - Specific target organ toxicity (single or repeated exposure)	

07/24/2018 EN (English US) 8/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Didecyldimethylammonium chloride (7173-51-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Tetrasodium ethylene diamine tetraacetate (64-02-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Citric acid (77-92-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Alcohols, C9-11, branched and linear, ethoxylated (68439-46-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

XU - XU - indicates a substance exempt from reporting under Chemical Data Reporting Rule
(formerly the Inventory Update Reporting Rule), i.e, Partial Updating of the TSCA Inventory

Data Base Production and Site Reports (40 CFR 711).

Quaternary ammonium compounds, benzyl-C12-16-alkyldimethyl, chlorides (68424-85-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

DECON-QUAT® 200C

This chemical is a pesticide product registered by the United States Environmental Protection Agency (10324-141-68959) and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below in Section 16. The pesticide label also includes other important information, including directions for use. Canada DIN #02374919.

Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Ethanol (64-17-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Revision date : 07/23/2018

Data sources : US OSHA HazCom (GHS) 25 May 2012.

Other information : Danger. Keep out of reach of children.

07/24/2018 EN (English US) 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapor	
H227	Combustible liquid	
H301	Toxic if swallowed	
H302	Harmful if swallowed	
H311	Toxic in contact with skin	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H319	Causes serious eye irritation	
H332	Harmful if inhaled	
H373	May cause damage to organs through prolonged or repeated exposure	
H400	Very toxic to aquatic life	
H401	Toxic to aquatic life	
H411	Toxic to aquatic life with long lasting effects	

Abbreviations and acronyms:

· · · · · · · · · · · · · · · · · · ·		
	ACGIH (American Conference of Government Industrial Hygienists)	
	ATE (Acute Toxicity Estimate)	
	CAS (Chemical Abstracts Service) number	
	DNEL (Derived No Effect Level)	
	EC50 (Effective Concentration 50%)	
	IARC (International Agency for Research on Cancer)	
	IATA (International Air Transport Association)	
	IMDG (International Maritime Dangerous Goods Code)	
	IMO (International Maritime Organisation)	
	LC50 (Lethal Concentration 50%)	
	LD50 (Lethal Dose 50%)	
	OECD (Organisation for Economic Co-operation and Development)	
	OSHA (Occupational Safety and Health Administration) (US)	
	PBT (Persistent, Bioaccumulative and Toxic)	
	PNEC (Predicted No Effect Concentration)	
	STEL (Short Term Exposure Limit)	
	TSCA (Toxic Substances Control Act) (US)	
	TWA (Time Weighted Average)	
	UNxxxx (Number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods)	
	vPvB (very Persistent and very Bioaccumulative)	

NFPA health hazard

NFPA fire hazard

: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can

: 0 - Material that in themselves are normally stable, even under fire conditions.

3 0

NFPA reactivity

07/24/2018 EN (English US) 10/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

* - Chronic (long-term) health effects may result from repeated overexposure

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection :

C - Safety glasses, Gloves, Synthetic apron

Indication of changes:

Section	Changed item	Change	Comments
1	Identification	Modified	
2	Hazards identification	Modified	
3	Composition/Information on ingredients	Modified	
4	First aid measures	Modified	
5	Fire fighting measures	Modified	
6	Accidental release measures	Modified	
7	Handling and storage	Modified	
8	Exposure controls / Personal protection equipment	Modified	
9	Physical and chemical properties	Modified	
10	Stability and reactivity	Modified	
11	Toxicological information	Modified	
12.	Ecological information	Modified	
14	Transport information	Modified	
15	Regulatory information	Modified	
16	Other information	Modified	

SDS US (GHS HazCom 2012)

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Veltek Associates, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Veltek Associates, Inc. accepts no liability for loss or damage resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

07/24/2018 EN (English US) 11/11