SAFETY DATA SHEET



1. Identification

Product identifier Presaturated wipes containing 70% Isopropyl alcohol, 30% water

Other means of identification

SDS number 7030LQSC

Product code 47751-458, 493650-239, CSPP0001, HCPS0002, HCPS0002IR, HCPS00044, HCPS1002,

HCPS2328, HCPS2328IR, HCPS6044, PRPS7030, PS-314, PS-314IR, PS-7030IR, PS-840IR, PS-850, PS-850E, PS-911, PS-911-12, PS-911EB, PS-911EB-12, PS-911LE, PSC20001, PSC20002, PSC20005, PSC20006, PSC20009, PSC20010, PSC20016, PSCP0001, PSCS0009, PSCS0012, PSCS0012B, PSG20002, PS-HS9-7030, PSME0001, PSPP0035, PSPP0039,

PSP90043, PSPS0044, PSPS0047, PSPS0073, PSPS0076, PSPS0077, PSPS0087, PSPS0091, PSPS0093, PSPS0094, PSTA0032, PSWE0001, PSWE0003, SAT C1 7030

PSPS0093, PSPS0094, PSTA0021, PSTA0022, PSWE0001, PSWE0003, SAT-C1-7030, SAT-C1-7030/18, SAT-C3-7030, SAT-C3-7030/18, SW420250, SW420951, SWC30170-PO,

SWNW0014R, SWNW0020

Recommended use Wipe for critical cleaning.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name Contec, Inc.

Address 525 Locust Grove

Spartanburg, SC 29303

USA

Telephone 1-864-503-8333
Email SDS@contecinc.com

Emergency phone number Call CHEMTREC day or night

USA/Canada: 1.800.424.9300

Mexico: 1.800.681.9531

Outside USA/Canada: +1.703.527.3887

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2A

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/eye

protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire:

Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Presaturated wipes containing 70% Isopropyl alcohol, 30% water
957603 Version #: 04 Revision date: 15-September-2023 Issue date: 10-August-2021

None known.

Supplemental information

Although the product as a whole is in solid format, the product does not meet the OSHA HCS definition of a flammable solid as per Appendix B to 1910.1200 - Physical Hazard Criteria, section B.7.1 and B. 7.2 or Canada's Hazardous Products Regulations Subpart 7.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Propan-2-ol	67-63-0	70
Other components below reportable levels		30

Composition comments

All concentrations are in percent by volume.

4. First-aid measures

Inhalation

Not relevant, due to the form of the product. However: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eve contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Not relevant, due to the form of the product. In case of ingestion: Rinse mouth. Get medical

attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Direct contact with eyes causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. In high concentrations, vapors are narcotic and may cause headache, fatigue, dizziness and nausea.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area, Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

May burn with invisible flame. Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread near ground to sources of ignition. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Carbon oxides. Organic compounds.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Cool containers exposed to flames with water. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Solid containing flammable liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Avoid contact with skin, eyes and clothing. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Avoid release to the environment. The liquid solvent solution is miscible in water.

Spills are very unlikely, because the wiper fabric has absorbed the liquid solvent solution. In the event of a spill, contain with an inert absorbent. Collect the wipes with a non sparking tool and absorb or wipe any residual liquids. Put material in suitable container.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Presaturated wipes containing 70% Isopropyl alcohol, 30% water

SDS US 957603 Version #: 04 Revision date: 15-September-2023 Issue date: 10-August-2021

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

WARNING! Used wipes may catch fire if improperly discarded or stored near ignition sources. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Avoid breathing mist/vapors. Avoid contact with skin, eyes and clothing. Avoid prolonged exposure. Wash thoroughly after handling. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Keep containers closed when not in use. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Components	Type	Value	
Propan-2-ol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
US. ACGIH Threshold Limit Value	s (TLV)		
Components	Туре	Value	
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
NIOSH. Immediately Dangerous to	Life or Health (IDLH) Values.	as amended	
Components	Type	Value	
Propan-2-ol (CAS 67-63-0)	IDLH	2 %	
		2000 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
	nical Hazards Type	Value	
US. NIOSH: Pocket Guide to Cher Components Propan-2-ol (CAS 67-63-0)		Value 1225 mg/m3	
Components	Туре		
Components	Туре	1225 mg/m3	

Biological limit values

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines Follow standard monitoring procedures.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Not necessary under normal conditions.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Neoprene. Polyvinyl chloride (PVC). Take note of the information given by the manufacturer concerning permeability and break through times, and of

special workplace conditions (mechanical strain, duration of contact).

Recommended materials: Polyethylene. Chlorinated polyethylene (or Chlorosulfonated polyethylene). Natural rubber. Nitrile rubber/Nitrile latex - NBR Ethyl vinyl alcohol laminate

("EVAL").

Unsuitable materials: Polyvinyl alcohol (PVA).

957603 Version #: 04 Revision date: 15-September-2023 Issue date: 10-August-2021

Skin protection

Other Wear suitable protective clothing.

concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Wear NIOSH approved respirator appropriate for airborne exposure at the point of use.

Check with respiratory protective equipment suppliers.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Wipes saturated with liquid.

Color Colorless.

Odor Alcohol-like.

Odor threshold Property has not been measured.

pH Property has not been measured. (liquid)

Melting point/freezing point Property has not been measured. (liquid)

Initial boiling point and boiling > 179.6 - < 192.2 °F (> 82 - < 89 °C) (liquid)

range

Flash point 68.9 °F (20.5 °C) (liquid)

Evaporation rate Property has not been measured. (liquid) **Flammability (solid, gas)** Wipes will burn if involved in a fire.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 2 % (liquid)

Explosive limit - upper (%) 12 % (liquid)

Vapor pressure43 hPa (32 mm Hg) (68 °F (20 °C) (liquid))Vapor densityProperty has not been measured. (liquid)

Relative density 0.872 (68 °F (20 °C) (liquid))

Solubility(ies)

Solubility (water)Soluble in water. (liquid)Partition coefficientNot applicable to mixtures.

(n-octanol/water)

Auto-ignition temperature 750.2 °F (399 °C) (liquid)

Decomposition temperature Property has not been measured.

Viscosity Property has not been measured. (liquid)

Other information

Density129.28 mg/m3Explosive propertiesNot explosive.

Kinematic viscosity Property has not been measured. (liquid)

Molecular weight Property has not been measured.

Oxidizing properties Not oxidizing.

Percent volatile 100 % (IPA)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Aldehydes. Halogenated organics. Halogens. Strong acids. Strong oxidizing agents.

Hazardous decomposition

products

Combustion may produce: Oxides of carbon and other organic substances.

11. Toxicological information

Information on likely routes of exposure

Inhalation No inhalation hazard under normal conditions. However: Prolonged inhalation of vapors may be

harmful. May cause drowsiness or dizziness. Headache. Nausea, vomiting.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Not relevant, due to the form of the product. However: Direct contact: Causes serious eye

irritation.

Ingestion Not relevant, due to the form of the product.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. In high concentrations, vapors are narcotic and may cause

headache, fatigue, dizziness and nausea.

Information on toxicological effects

Acute toxicity

Not relevant, due to the form of the product in its manufactured and shipped state.

Components Species Test Results

Propan-2-ol (CAS 67-63-0)

<u>Acute</u>

Dermal

LD50 Rabbit 12870 mg/kg

Inhalation

Vapor

LC50 Rat 72.6 mg/l, 4 hours

Oral

LD50 Rat 4710 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Not relevant, due to the form of the product. However: Direct contact: Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Propan-2-ol (CAS 67-63-0) 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified. However: In high concentrations, vapors are narcotic and may cause headache,

fatigue and nausea.

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Frequent or prolonged contact may defat and dry the skin.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Propan-2-ol (CAS 67-63-0)

Aquatic

Acute

Crustacea LC50 Daphnia magna > 10000 mg/l, 24 hours
Fish LC50 Pimephales promelas 9640 mg/l, 96 hours

Chronic

Crustacea EC50 Daphnia magna > 100 mg/l, 21 days

NOEC Daphnia magna 141 mg/l, 16 days

30 mg/l, 21 days

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential Bioconcentration potential is low.

Partition coefficient n-octanol / water (log Kow)

Propan-2-ol (CAS 67-63-0) 0.05

Mobility in soil Isopropyl alcohol is highly mobile in soil.

Other adverse effects

The product contains a volatile organic compound which has a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in

accordance with all applicable regulations. Used wipes must be disposed in a closed container.

Dispose of used wipes by dry waste to landfill.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

Contaminated packaging

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number UN3175

UN proper shipping name

Transport hazard class(es)

Solids containing flammable liquid, n.o.s. (Isopropanol), Limited Quantity

Class 4.1
Subsidiary risk Label(s) 4.1
Packing group ||

Environmental hazards

Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 47, IB6, IP2, T3, TP33

Packaging exceptions151Packaging non bulk212Packaging bulk240

IATA

UN number UN3175

UN proper shipping name Solids containing flammable liquid, n.o.s. (Isopropanol)

Transport hazard class(es)

Class 4.1
Subsidiary risk Packing group II
Environmental hazards No.
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3175

UN proper shipping name SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Isopropanol), Limited Quantity

Transport hazard class(es)

Class 4.1
Subsidiary risk Packing group || Environmental hazards

Marine pollutant No EmS F-A, S-I

F-A, 5-I

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Insport in bulk according to Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Propan-2-ol (CAS 67-63-0) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated

"active"

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Serious eye damage or eye irritation

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 Propan-2-ol
 67-63-0
 70

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Propan-2-ol (CAS 67-63-0) Low priority

US state regulations

US. Massachusetts RTK - Substance List

Propan-2-ol (CAS 67-63-0)

US. New Jersey Worker and Community Right-to-Know Act

Propan-2-ol (CAS 67-63-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Propan-2-ol (CAS 67-63-0)

SDS US

957603 Version #: 04 Revision date: 15-September-2023 Issue date: 10-August-2021

US. Rhode Island RTK

Propan-2-ol (CAS 67-63-0)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

Australian Inventory of Industrial Chemicals (AICIS)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

On inventory (yes/no)*

Propan-2-ol (CAS 67-63-0)

International Inventories

Australia

Country(s) or region

/ lastrana	Additional inventory of industrial orienticals (Aloro)	103
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Inventory name

Issue date 10-August-2021 **Revision date** 15-September-2023

Version # 04

NFPA ratings



Disclaimer

Contec, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

SDS US 8/8 957603 Version #: 04 Revision date: 15-September-2023 Issue date: 10-August-2021