MSDS for #7405 Test Tube/Syringe Rack

WIRE SPECIALTY MFG., LLC 7101 – 143RD AVENUE NW; SUITE I RAMSEY, MN. 55303 (763) 576-0500

MATERIAL ANALYSIS CERTIFICATION

I. PRODUCT IDENTIFICATION:

GOVESAN, S.A. NAME:

RPB-1130; RAL 1013

COLOR: OYSTER WHITE

CHEMISTRY: POLYESTER TGIC

DOT PROPER SHIPPING NAME: NOT A REGULATED MATERIAL.

UL APPROVED: MH25283 (N)

II. HMIS RATINGS FOR HAZARDOUS INGREDIENTS:

HEALTH: 1

FLAMMABILITY: 1

REACTIVITY: 0

FOR PPE (PERSONAL PROTECTION EQUIPMENT) PLEASE REFER TO OCCUPATIONAL CONTROL PROCEDURES.

II. HAZARDOUS INGREDIENTS:

MATERIAL NAME / C.A.S.	LEVEL IN PRODUCT	OSHA PEL	ACGIH TLV
TITANIUM DIOXIDE (13463-67-7)	<or 60%<="" =="" td=""><td>10.0 MG/M3</td><td>10.0 MG/M3</td></or>	10.0 MG/M3	10.0 MG/M3
CALCIUM CARBONATE (471-34-1)	<or 6%<="" =="" td=""><td>15.0 MG/M3</td><td>10 MG/M3</td></or>	15.0 MG/M3	10 MG/M3
SILICA AMORPHOUS (7631-86-9)	<or 2%<="" =="" td=""><td>6.0 MG/M3</td><td>6.0 MG/M3</td></or>	6.0 MG/M3	6.0 MG/M3
TGIC (2431-62-9)	<or 5%<="" =="" td=""><td>NE¹</td><td>NE</td></or>	NE ¹	NE

III. PHYSICAL DATA:

PHYSICAL STATE: SOLID
BOILING RANGE: N/A
PH: N/A
% VOLATILE BY WEIGHT: N/A
WEIGHT PER GALLON: N/A

IV. FIRE PROTECTION:

FLASH POINT METHOD:

N/A

APPROPRIATE

DRY CHEMICAL, SAND OR GROUND LIMESTONE

EXTINGUISHERS:

SPECIAL FIRE FIGHTING

PERSONS EXPOSED TO PRODUCTS OF

PROCEDURES:

COMBUSTION SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT. DO NOT ALLOW POWDER TO BE

¹ NE = NOT ESTABLISHED

MSDS for #7405 Test Tube/Syringe Rack

WIRE SPECIALTY MFG., LLC 7101 – 143RD AVENUE NW; SUITE I RAMSEY, MN. 55303 (763) 576-0500

MATERIAL ANALYSIS CERTIFICATION

DISPERSED INTO THE AIR WHILE FIGHTING

FIRES.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

DUST MIXTURES IN AIR MAY BE FLAMMABLE.

· HAZARDOUS

DECOMPOSITION PRODUCTS:

INCOMPLETE COMBUSTION CAN YIELD LOW MOLECULAR WEIGHT HYDROCARBONS AND

CARBON MONOXIDE.

HAZARDOUS

POLYMERIZATION:

WILL NOT OCCUR.

V. EFFECTS OF OVEREXPOSURE:

ACUTE:

POWDER COATINGS MAY IRRITATE THE SKIN OR

RESPIRATORY TRACT IN SENSITIVE INDIVIDUALS. EYE CONTACT MAY BE

ABRASIVE. MAY CAUSE SKIN, EYES, NOSE AND

THROAT.

EXISTING HEALTH

CONDITIONS:

INHALATION OF DUST MAY AGGRAVATE LUNG CONDITIONS SUCH AS ASTHMA, EMPHYSEMA OR CHRONIC BRONCHITIS.

VI. EMERGENCY AND FIRST AID PROCEDURES:

FOR EYE CONTACT:

FLUSH EYE IMMEDIATELY WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL

ATTENTION.

FOR SKIN IRRITATION:

WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE FROM EXPOSURE. KEEP WARM AND

■ INHALATION:

STILL. NOTIFY A PHYSICIAN.

VII. OCCUPATIONAL CONTROL PROCEDURES:

EYE PROTECTION:

SAFETY GLASSES, EYE WASH.

SKIN PROTECTION:

GLOVES, LONG SLEEVES SHIRT AND OTHER CLOTHING AS NEEDED TO MINIMIZE SKIN

CONTACT.

RESPIRATORY PROTECTION:

NIOSH APPROVED PARTICULATE RESPIRATOR.

VENTILATION:

LOCAL EXHAUST WITH AN APPROPRIATE DUST

COLLECTION SYSTEM.

VIII. SPILL, LEAK AND DISPOSAL PROCEDURES:

SPILL OR LEAK PROCEDURES: REMOVE ALL SOURCES OF IGNITION, VACUUM

OR SWEEP UP SPILLED MATERIAL.

MSDS for #7405 Test Tube/Syringe Rack

WIRE SPECIALTY MFG., LLC 7101 – 143RD AVENUE NW; SUITE I RAMSEY, MN. 55303 (763) 576-0500

MATERIAL ANALYSIS CERTIFICATION

■ WASTE DISPOSAL:

THIS PRODUCT DOES NOT MEET THE DEFINITION OF HAZARDOUS WASTE AS DEFINED IN 40 CFR 261. INCINERATE OR LANDFILL IN ACCORDANCE WITH LOCAL OR STATE REGULATIONS.

IV. ADDITIONAL INFORMATION:

- STORE IN A COOL, DRY LOCATION.
- **AFTER HANDLING THE PRODUCT, WASH THOROUGHLY BEFORE EATING OR SMOKING.**
- USE ADEQUATE VENTILATION OR NIOSH APPROVED ORGANIC VAPOR RESPIRATOR WHEN WELDING, CUTTING OR BRAZINE COATED PARTS.

X. REGULATORY INFORMATION:

TSCA: WE CERTIFY THAT ALL COMPONENTS OF THIS PRODUCT ARE REGISTERED UNDER THE REGULATIONS OF THE TOXIC SUBSTANCE CONTROL ACT.

SARA: THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICAL SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT 1986 (SARA) AND 40CFR PART 372:

MATERIAL NAME / C.A.S.	PERCENTAGE	
TITANIUM DIOXIDE (13463-67-7)	<or -="" 60%<="" td=""></or>	
CALCIUM CARBONATE (471-34-1)	<or 6%<="" =="" td=""></or>	
SILICA AMORPHOUS (7631-86-9)	<OR = 2%	
TGIC (2431-62-9)	<or 5%<="" =="" td=""></or>	

THIS INFORMATION IS TAKEN FROM SOURCES OR IS BASED UPON BELIEVED TO BE REALIABLE AND IS SUPPLIED IN GOOD FAITH BY WIRE SPECIALTY MFG., LLC.

HOWEVER, WIRE SPECIALTY MFG., LLC MAKES NO WARRANTY AS TO THE ABSOLUTE CORRECTNESS OR SUFFICIENCY OF ANY OF THE FOREGOING OR THAT ADDITIONAL OR OTHER MEASURES MAY NOT BE REQUIRED UNDER PARTICULAR CONDITIONS. WIRE SPECIALTY MFG., LLC SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGE DIRECTLY OR INDIRECTLY RESULTING FROM THE USE OF ANY OF ITS PRODUCTS AND WIRE SPECIALTY MFG., LLC ASSUMES NO OBLIGATION OR LIABILITY FOR THE RELIANCE ON THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.